

OIL Mobile Home Furnace OME Series



- 16-gauge aluminized steel octatherm heat exchanger
- 22-gauge powder coated cabinet for durability
- Top-quality controls and control system
- Insulated blower compartment
- Easy-access clean-out ports
- Easy access, easy cleaning, permanent, washable ilter
- Lifetime limited heat exchanger warranty
- 10-year parts warranty

MODEL NO.	OME-72D36 / OME-72T36*	
	LOW FIRE	HIGH FIRE
HEAT INPUT RATE (BTUH)	70,000	85,000
OUTPUT (BTUH)	60,000	72,000
SEASONAL EFFICIENCY	86%	
TEMP RISE	66º	
LARGEST REC A/C	2 RODT 8	
VENT PIPE SIZE (IN.)	4"	
DIEMENSIONS WxDxH (IN.)	18 x 24-3/4 x 57	
SUPPLY AIR OUTLET WxDxH (IN.)	12" x 12"	
APPROX. SHIPPING WEIGHT (LBS.)	240 LBS.	
* ECM blower motor	ACCESSIORIES	
MOBILE HOME BASE	70-BASE	
COTTAGE BASE	OICOT-BASE	
COIL CABINET FOR 2-3 TONS	CEIIIS	
ROOF JACK 12" OR LESS	TRJ-1	
ROOF JACK 13" TO 24"	TRJ-2	
ROOF JACK 25" TO 36"	TRJ-3	
VENT PIPE	VP-1	
SLOPE ADAPTOR 2-1/2 - 12	TSA-25	
SLOPE ADAPTOR 3-1/2 - 12	OE-AZT	
COMBUSTION AIR INTAKE HOOD	ADPS7402	
ROOF JACK COMBUSTION AIR KIT	ADPS7512	
OFFSET VENT KIT	AOPS7518	





